

TARIME TOWN COUNCIL					
SCHEDULES OF MATERIALS OF WINDOWS, DOORS AND PARTITIONS FOR THE PROPOSED COMPLETION OF TARIW TOWN COUNCIL ADMINISTRATION BLOCK MARCH 2022					
ITEM	GENERAL DESCRIPTIONS OF WORKS	QTY	UNIT	RATE	AMOUNT
	WINDOWS				
	Supply and fix Composite Aluminium windows units as microns manufactured; comprising 30x75mm frame sliding casement with 30x75mm stile and rails compartment fished with 21 micron silver anodized aluminium alloy matt finished including assembling bedding frame in proprietary bedding compound and screws pointing externally with mastic and stripping protective tape on aluminium frame mullions and transoms and including unblocking devices where necessary;				
1	2520 x 1800mm high divided into 4No panels consist of 2No casement shutters with 6mm tinted glass and mosquito gauze; (TYPE-W1)	5	No		
2	2270 x 1800mm high; ditto; (TYPE-W2)	10	No		
3	1800 x 1800mm high; ditto; (TYPE-W3)	104	No		
4	1270 x 1800mm high; ditto; (TYPE-W4)	4	No		
5	1200 x 1200mm high; ditto; (TYPE-W5)	16	No		
6	800 x 1800mm high; ditto; (TYPE-W6)	4	No		
7	800 x 1580mm high; ditto; (TYPE-W7)	2	No		
8	800 x 1200mm high; ditto; (TYPE-W8)	2	No		
9	1200 x 1800mm high; ditto; (TYPE-W9)	4	No		
10	800 x 1800mm high; ditto; (TYPE-W10)	2	No		
11	500 x 600mm high; ditto; (TYPE-DW2)	4	No		
	Curtains:				
12	Venetia vertical blinds to windows including all fixing accessories as per manufacture's specifications and Architect's instructions	534	M2		
	SUPPLY AND FIX ALUMINIUM PARTITION				
1	2270x3125mm high; filled with 12mm thick MDF board laminated both sides bottom pannels; 6mm thick georgian wire glass at the middle and 6mm thick clear glass on top	1	No		
2	3270x3125mm;high; filled with 12mm thick MDF board laminated both sides bottom pannels; 6mm thick georgian wire glass at the middle and 6mm thick clear glass on top	1	No		
	SUPPLY AND FIX ALUMINIUM DOORS				

	<p><u>Supply and fix Aluminium doors and frame in either anatural anodized or mill or polyster finish to architect approval manufactured from ALUMINIUM ALLOY TO bs 1474 (1969) & weather tested to BS 4315 part (1968) components as manufactures and assembled by approved manufactures, including clumping, mullions and transoms factory glazing, weather stripping concealed overhead spring closures pull handles to both sides and manufacture's floor sops, including assembling of units of site stripping protective tapes and fixing with manufacture, screws and proprietary bedding compounds to structural openings</u></p>				
1	(D1) 2770 x 2825 mm high double door with vent lights, complete with overhead door closer; 2 pairs of push/pull handle; 2No 150mm top and bottom bolts. 1 No lockset, glazed with 6mm wire glass	1	PC'S		
2	(Dw1) 2770 x 2825 mm high double door with vent lights, complete with overhead door closer; 2 pairs of push/pull handle; 2No 150mm top and bottom bolts. 1 No lockset, glazed with 6mm wire glass	2	PC'S		
SUB-TOTAL WINDOWS					